




HKB-650F 自润滑翻边轴套

HKB-650F Metric Flange Bushes




Mating Housing
相配座孔

单位Unit: mm

内径		外径		法兰		长度 L _{±0.1}							
∅ d		∅ D		F	t	10	12	15	17	18	20	23	25
6	+0.032 +0.020	10	+0.028 +0.019	16		0610	0612						
8	+0.040 +0.025	12		20	2	0810	0812	0815					
10		14	+0.034 +0.023	22		1010	1012	1015	1017		1020		
12		18		25		1210	1212	1215			1220		1225
13		19		26		1310	1312	1315			1320		1325
14	+0.050 +0.032	20		27	3			1415			1420		1425
15		21	+0.041 +0.028	28		1510	1512	1515			1520		1525
16		22		29			1612	1615		1618	1620	1623	1625
18		24		32				1815			1820		1825
20		30		40				2015			2020		2025
25	+0.061 +0.040	35		45				2515			2520		2525
30		40	+0.050 +0.034	50							3020		3025
31.5		45		60	5						3120		
35		50		65							3520		3525
40	+0.075 +0.050	55		70							4020		4025
45		60	+0.060 +0.041	75	0 -0.1								
50		65		80									
55		75	+0.062 +0.043	85									
60		80		95	7.5								
63	+0.090 +0.060	85		105									
65		90	+0.073 +0.051	110									
70		100		120									
75		110	+0.076 +0.054	130									
80	+0.107 +0.072	120		150									
90		140	+0.088 +0.063	170	10								
100		150	+0.090 +0.065	180									
120		160		190									
130	+0.125 +0.085	170	+0.093 +0.068	200									
140		180		210									

HKB-650F 自润滑翻边轴套
HKB-650F Metric Flange Bushes



Mating Shaft
相配轴

d8: High load 高负荷
 e7: Light load 轻负荷
 f7: High precision 高精度

材质	高力黄铜 + 固体润滑剂
Material	650#+Graphite

单位Unit: mm

长度 L _{±0.03}									压入后 内径公差	内径 Ø d
30	35	40	50	60	67.5	80	100	120		
									+0.016 +0.004	6
									+0.021 +0.006	8
									+0.031 +0.013	10
1230										12
1330										13
										14
1530									+0.026 +0.008	15
1630	1635	1640								16
1830	1835	1840								18
2030	2035	2040							+0.037 +0.016	20
2530	2535	2540	2550						+0.032 +0.011	25
3030	3035	3040	3050							30
3130	3135	3140								31.5
3530	3535	3540	3550						+0.046 +0.021	35
4030	4035	4040	4050							40
4530	4535	4540	4550	4560					+0.040 +0.015	45
5030	5035	5040	5050	5060					+0.055 +0.025	50
		5540		5560						55
		6040	6050	6060		6080			+0.053 +0.023	60
					6367					63
				6560						65
			7050			7080				70
				7560					+0.046 +0.016	75
				8060		8080	80100			80
				9060		9080			+0.060 +0.025	90
						10080	100100		+0.052 +0.017	100
						12080	120100			120
						13080	130100		+0.068 +0.028	130
						14080	140100			140
							150100	150120	+0.065 +0.025	150
							160100	160120		160